

Do Kadam Aage...

New
75 HP 4WD
Model 5075 E

Now with
PowerReverser™



Forward - Reverse tractor
without operating clutch and gear



Saves time, increases productivity!

Warranty on Engine*
2+1 Years
or 3000 hours*

*Conditions apply



Suitable for Loader,
Dozer and Leveling Applications



Wide Range of Speed



On Wet Clutch



Electro-Hydraulic Wet Clutch

Zindagi ka
Best Decision!™



JOHN DEERE

Technical Specifications

ENGINE

Type	: 75 HP, 2400 RPM, 3 Cylinders, Direct injection, Turbo charged, Rotary FIP, Liquid cooled with over flow reservoir
Air filter	: Dry type, Dual element

TRANSMISSION

Clutch	: Dual, Wet Clutch Technology, Suspended type pedals, Electro-Hydraulic Operation,
Gear box	: 12 Forward + 12 Reverse : Top Shaft Synchromesh
Speeds	: Forward 1.7 - 35.1 kmph Reverse 1.8 to 38.3 Kmph
Forward & Reverse	: Through lever on steering column

BRAKES

	: Self adjusting and self equalising, hydraulically actuated, Oil immersed disc brakes
--	--

HYDRAULICS

Lifting capacity	: 1800 kg at lower link ends
3 point linkage	: Category - II ADDC

STEERING

Type	: Power
------	---------

POWER TAKE OFF

Type	: Electro-Hydraulic Wet Clutch Dual, Independent, 6 Splines
Standard	: 540 @ 2376 ERPM
Economy	: 540 @ 1705 ERPM

WHEELS AND TYRES

Front	: 12.4 X 24, 8 PR
Rear	: 18.4 X 30, 12 PR

FUEL TANK

Capacity	: Rear mounted, 68 L
----------	----------------------

ELECTRICAL SYSTEM

	: 85 Ah, 12 V battery, 43 Amp. Alternator, 12 V, 2.5 kW Starter motor
Instrument cluster	: LCD display (Hour meter, Tractor speed and PTO RPM monitor)

WEIGHT AND DIMENSIONS

Total weight	: 2600 kg
Wheel base	: 2050 mm
Overall length	: 3630 mm
Overall width	: 1850 mm

ADDITIONAL FEATURES

- Finger-Touch Electro-Hydraulic Forward Reverse Lever with Neutral
- Maintenance-free Wet Clutch Technology
- Heavy Duty Front and Rear Axle
- Car type Engine On/Off
- ROPS - Roll over protection system

5075 E also available in base model without PowrReverser™

New
75 HP 4WD
Model 5075 E

Now with

PowrReverser™



Automatic hood opening
Single piece hood opening
with gas struts



Finger guard
Enhanced safety



Side bar & steps with mat
Climbing up and
down the tractor
is now easier



Operator Presence Switch
Tractor will not move
if there is no operator on seat



**Electro-Hydraulic
Operated
PTO Switch**



**High torque
reserve**
More productivity

John Deere Genuine Parts

| Economical | Reliable |
| Easily available |



For more information, please contact our authorised dealer or nearest area office.

John Deere India Private Limited
3rd floor, Tower-15, Cybercity, Magarpatta City,
Hadapsar, Pune - 411013. Maharashtra.

Please note: Improvement in the product is a continuous process.
Hence the information given in this brochure is subject to change without prior notice.

Accessories shown are not the part of standard equipment.

 **JOHN DEERE**

• Tractors • Farm Equipment • Finance

www.JohnDeere.co.in